### CHAPTER 5: GUIDELINES FOR REHABILITATION OF EXISTING AUTO-ORIENTED BUILDINGS

LANDSCAPING				21
BUILDING MATERIALS				21
PARKING LOCATION				21
ROOFS			•	22
WINDOWS		•	•	22

# CHAPTER 5: GUIDELINES FOR REHABILITATION OF EXISTING AUTO-ORIENTED COMMERCIAL BUILDINGS

#### LANDSCAPING

- 40. ESTABLISH OR MAINTAIN A YARD IMAGE IN FRONT OF SET-BACK BUILDINGS WHERE FEA-SIRLE
- Provide landscaping in the "interior" of parking lots.

#### BUILDING MATERIALS


#### Policy:

Building materials of auto-oriented businesses should relate to the historic Village materials.

#### Guideline:

- 41. USE BRICK OR STUCCO AS THE PREDOMI-NANT FACADE MATERIALS IN RENOVATIONS.
- Red brick is encouraged.
- Rough-textured stucco similar to "Pebbledash" is also appropriate. See Appendix A in Book 3.

#### PARKING LOCATION



Guideline 42. Covered parking was included behind the Village stores building that was located at the Plaza and Brook Street.

#### Policy:

Historically, parking was planned to be placed behind buildings and was therefore visually subordinate to the Village/lawn character. Therefore the visual impact of cars today should be minimized.

#### Guidelines:

42. LOCATE PARKING LOTS TO THE SIDE OR REAR OF BUILDINGS WHERE FEASIBLE.

### 43. DEVELOP SHARED LOTS AND DRIVEWAYS AMONG LOTS WHERE FEASIBLE.

- This will help to minimize the number of curb cuts and pedestrian crossing conflicts.
- Buffer edges with landscaping.
- See also Guidelines for Site Design Guidelines in Book 1.

#### ROOFS

#### 44. ROOFS MAY BE FLAT OR SLOPING

- Sloping roofs should be in the proportions/ slopes of those used historically.
- · Gabled roofs are strongly encouraged.
- · Roofs should be a muted red color.


#### WINDOWS

### 45. WINDOW PROPORTIONS SHOULD MATCH THOSE USED HISTORICALLY.

- Vertically proportioned windows should be used.
  These may be grouped in sets to establish larger window areas.
- See also Guidelines for Signs, Book 1:

## 46. ADAPTATIONS OF HISTORIC DETAILS ARE ENCOURAGED IN THE REHABILITATION OF AUTO-ORIENTED COMMERCIAL BUILDINGS.

- Consider brick quoins at building corners.
- Consider using wood "strap-work" to trim windows and delineate horizontal elements.
- See Appendix A, Book 3, for historic design elements.



Guideline 45. Window proportions should match those used historically. (Design for Apartments and Reading Room at Lodge Street and Biltmore Road.)